

Appl. No. 09/981,089
Amdt. dated August 23, 2004
Reply to Office action of Feb. 23, 2004

Amendments to the Specification:

Please replace paragraph [0036.1] with the following amended paragraph:

[0036.1] FIG. 17A is a front view of the window wrap of FIG. 10 installed in a rough window frame.

Please add the following new paragraph after paragraph [0036.1] and before paragraph [0036.2]:

[0036.11] FIG. 17B is a side view of the window wrap of FIG. 17A installed in a rough window frame.

Please replace paragraph [0036.2] with the following amended paragraph:

[0036.2] FIG. 18 is a cross-section taken along line 18-18 of the window wrap installed in a rough window frame of FIG. 17A.

Please replace paragraph [0055] with the following amended paragraph:

[0055] The window wrap may then be inserted, as a unit, directly into the rough window frame. It is preferred that an adhesive be used between the rear surface 202 of the wall extensions 302 and the rough frame. However, a trim channel or caulk may also be used between the window wrap and the rough window frame. The use of adhesive allows for settlement of the window wrap, reduces the chance of cracking at the corners of the window wrap, and provides an almost airtight seal between the window wrap and the frame. The drywall panels on the framing wall around the window frame may then be inserted into the space 114 of the wall extension 302 of the window wrap, as shown in ~~FIG. 17~~ FIGS. 17A and 17B.